HANDHELD SCANNER

- Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice.
- ZEBEX is the trademark of ZEBEX INDUSTRIES INC, all rights reserved.



Z-3191LE NEW

Handheld Gun Type Laser Scanner

Defy harsh environment with the new gun type laser scanner. Featuring elastic rubber protection and durable large size trigger users can operate the scanner with comfort and protection, even during prolonged periods of use. Embedded with ZEBEX' most advanced decoding technology, Z-3191LE decodes at 75 scans per second and is able to recognize most of the 1D barcodes on the market including GS1 DataBar. Reliable and proven to maintain performance through cruel conditions, it is designed for users requiring sharp scanning performance and industrious applications.

- 32 bit proprietary **Ultrascan** decoding technology
- GS1 DataBar decoding capability
- Auto Gain Control
- Synthetic rubber handle for operation comfort and durability





OPERATIONAL

650 nm visible laser diode (VLD) 32 bit 4 mil: 0 – 10 mm 5 mil: 20 – 90 mm 7.5 mil: 10 – 200 mm 10 mil: 10 – 230 mm 13 mil: 30 – 250 mm 20 mil: 50 – 380 mm 100 scans per second 38° 30% @ UPC/EAN 100% Beeper and LED Beeper tone & volume Keyboard, RS-232, HID USB, USB Virtual COM, wand, OPOS, JPOS
4 mil: 0 – 10 mm 5 mil: 20 – 90 mm 7.5 mil: 10 – 200 mm 10 mil: 10 – 230 mm 13 mil: 30 – 250 mm 20 mil: 50 – 380 mm 100 scans per second 38° 30% @ UPC/EAN 100% Beeper and LED Beeper tone & volume
5 mil: 20 - 90 mm 7.5 mil: 10 - 200 mm 10 mil: 10 - 230 mm 13 mil: 30 - 250 mm 20 mil: 50 - 380 mm 100 scans per second 38° 30% @ UPC/EAN 100% Beeper and LED Beeper tone & volume
38° 30% © UPC/EAN 100% Beeper and LED Beeper tone & volume
30% @ UPC/EAN 100% Beeper and LED Beeper tone & volume
Beeper and LED Beeper tone & volume
Beeper tone & volume
·
Keyboard, RS-232, HID USB, USB Virtual COM, wand, OPOS, JPOS
147.0 × 62.0 × 114.5 mm (device only)
140 g (device only)
Field replaceable, standard 2M straight
5 VDC ±5%
0.9 watts
Max. 180 mA
65 mA
CE & FCC DOC compliance, VCCI, BSMI
IEC 60825-1 Class 2
0°C – 50°C (32°F – 122°F)
-10°C – 70°C (14°F – 158°F)
5% – 95% RH (non-condensing)
Max. 4,500 Lux (fluorescence)
Designed to withstand 1.2M drops
IP41
UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39, Codabar, Code 128 & EAN 128, Code 93, ITF 2 of 5, IATA Code, MSI, China Postal Code, Code 32, Industrial 2 of 5, Standard 2 of 5, JAP, Code 11, GS1 DataBar, GS1 DataBar Limited, GS1 DataBar Expanded, Telepen

2

2. Clear LED indicators 3. Optional adjustable stand

1. Ergonomic gun-type handle & large trigger

ZEBEX

