

Wireless Scanner



XL-9309



- ⊙ 300m communication distance
- ⊙ Simple pairing by scanning one code
- ⊙ 1 base frame can support 99 scanners
- ⊙ Ensure 100% successful data transmission
- ⊙ With memory, can store 100,000 EAN-13 code
- ⊙ Full independent intellectual property rights
- ⊙ One full charge support 100,000 times scanning



Light Source	Visible Laser Diode 650m	Size	L x W x H:170mm x 71mm x 98mm
Scan Pattern	Single Scan & Manual	Charge Mode	Wired charging
Working Frequency	433 MHz ISM frequency	Weight	180g
Communication distance	Up to 300m at open places	Material	ABS+PC
Scan Precision	3mil(pcs0.9)	Voltage	2200 mAh/DC 5V
Scan Rate	300 times/scend	Operating Current	110mA/35mA
Scan Width	30mm@scan window,220mm@200m	EMC	CE & FCC DOC compliance
Depth of Scan Field	0-280mm(0.33mm pcs0.9)	IP Standard	IP54
Scan Angle	30° & 65° & 55°	Decoding Capability	all 1D barcode including GS1
Communication Distance	300m	Humidity	5% to 95% relative humidity
Print Contrast	20% UPC/EAN 100%	Shock	1.5M drops
Decoding Capability	EAN-8,EAN-13,UPC-A,UPC-E,Code11,Code 32,Code39 Standard,Code39 Full Ascii,Code 93,Code128,EAN128, UPC-A, UPC-E,EAN/UPC +2/+5,Codabar, Industrial 25,Industrial 2of 5,Interleave 25, Interleave 2of5, Matrix 25, Matrix 2 of 5,MSI/Plessey, UK/Plessey,ISBN,ISSN,GS1-rss14,GS1-Limited,GS1-Expanded,GS1 STACKChina post 25,etc.		



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com