



Z-3100

Advanced Middle-Range Handheld CCD Scanner



Z-3100 is the upgraded version of ZEBEX middle-range handheld CCD scanner with faster scan rate, longer scanning depth and better decoding ability. At a superior rate of 330 scans per second, ZEBEX proprietary **Ultrascan** hardware decoding technology empowers Z-3100 to decode the majority of 1D barcodes as well as GS1 DataBar. It has working range up to 300 mm and is able to decode a barcode wider than 102 mm.

- Proprietary **Ultrascan** decoding technology
- Streamline design and Large trigger for effortless operation
- 32-bit micro processor unit
- Analog image capture technology
- Support presentation scan mode
- 0 – 100,000 Lux light immunity
- Captures barcodes on mobile phone, tablet, or computer screens

1. Sleek lines in a simple form factor and ergonomic grip
2. Optional rubber holder
3. Optional adjustable stand



- Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice.
- **ZEBEX** is the trademark of ZEBEX INDUSTRIES INC, all rights reserved.

OPERATIONAL

Light Source	617 nm visible red LED	
Optical System	Linear CCD array	
Microprocessor	32-bit	
Depth of Field	4 mil: 0 – 60 mm 7.5 mil: 0 – 180 mm 13 mil: 0 – 300 mm	5 mil: 0 – 100 mm 10 mil: 0 – 220 mm 20 mil: 0 – 350 mm
	<i>(Note: DOF may vary depending on environment condition and barcode quality.)</i>	
Scan Rate	330 scans per second	
Scan Angle	42°	
Print Contrast	Min. 30% @ UPC/EAN 100%	
Indicator	Blue LED	
Beeper Operation	Programmable tone & beep time	
System Interface	Keyboard, RS-232, HID USB, USB Virtual COM, wand, OPOS, JPOS	

PHYSICAL

Dimension	152.3 × 64.4 × 104.9 mm (device only)
Weight	84 g (device only)
Cable	Standard 2M straight

POWER

Input Voltage	5 VDC ±10%
Operating Current	110 mA typical

REGULATORY

EMC	CE & FCC DOC compliant, VCCI, BSMI
Safety	IEC 62471 Exempt

ENVIRONMENTAL

Operating Temperature	0°C – 50°C (32°F – 122°F)
Storage Temperature	-20°C – 60°C (-4°F – 140°F)
Humidity	5% – 95% RH (non-condensing)
Light Level	0 – 100,000 Lux
Drop Durability	Designed to withstand 1.5M drops

DECODING CAPABILITY

1D Barcode	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39, Codabar, Code 128 & EAN 128, Code 93, ITF 2 of 5, IATA Code, MSI, China Postal Code, Code 32, Industrial 2 of 5, Standard 2 of 5, JAP, Code 11, GS1 DataBar, GS1 DataBar Limited, GS1 DataBar Expanded, Telepen
------------	---

